

8 Channel Coarse Wavelength Division Multiplexer

(patent pending)

Product Description

Agiltron's Wavelength Division Multiplexer (WDM) is based on thin film filter technology. This proven technology offers wide channel bandwidth, flexible channel configuration, low insertion loss, and high isolation. The CWDM series modules are used to add or drop a particular wavelength and are ideal for telecommunications and networking. Agiltron's CWDM modules are Bellcore GR -1221 qualification tested and are epoxy-free in the optical path.



Performance Specifications

Parameter	Mux	Demux
Operating Wavelength (nm)	1470 to 1610	
Center Wavelength Accuracy (nm)	± 0.5	
Channel Spacing (GHz)	20	
Channel Passband (@-0.5dB bandwidth)(nm)	≥13	
Insertion Loss (dB) ¹	≤ 2.2	
Channel Uniformity (dB)	≤ 1.0	
Channel Ripple (dB)	≤ 0.3	
Isolation (dB)	Adjacent	N/A
	Non-adjacent	≥40
Insertion Loss Temperature Sensitivity (dB/° C)	≤ 0.003	
Wavelength Temperature Shifting (nm/° C)	≤ 0.002	
Polarization Dependent Loss (dB)	≤ 0.1	
Polarization Mode Dispersion (ps)	≤ 0.1	
Directivity (dB)	≥ 50	
Return Loss (dB)	≥ 45	
Power Handling (mW)	300	
Operating Temperature (° C)	0 ~ +70	
Storage Temperature (° C)	-40 ~ +85	
Dimensions (mm)	L110 x W95 x H7.5	

1. Excluding connectors

Features

- High Channel Isolation
- Low Insertion Loss
- Highly Stable & Reliable
- Epoxy-Free Optical Path
- Low Profile Packaging

Applications

- Line Monitoring
- WDM Network
- Telecommunication
- Cellular Application
- Fiber Optical Amplifier
- Access Network

8 Channel Coarse Wavelength Division Multiplexer

Ordering Information

CWDM-	C	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	Ch. Spacing	Number of channel	Configuration	1st ITU Channel	Pigtail Style	Fiber Length	Connector
	CWDM Grid=C	8 Channel=08	Mux=M Demux=D	1470nm=470 1471nm=471 1571nm=571	Bare Fiber=1 900um Jacket=2 Special=0	0.25M=1 0.5M=2 1.0M=3 Special=0	None=1 FC/PC=2 FC/APC=3 SC/PC=4 SC/APC=5 ST/PC=6 LC=7 Special=0