


0.7 mm Movement Free Space etMEMS™ Attenuator Sub-mount



(Protected by US patent 10752492B2)

DATASHEET

BUY NOW



Features

- Compact
- High Reliability
- Direct drive
- Low IL, PDL, WDL & TDL
- Intrinsic tolerance to ESD

Applications

- Power Control
- Power Regulate
- Channel Balance
- Instrumentation

The etMEMS™ series of free space variable optical attenuator (FS-VOA) is based on a proprietary patent pending micro-electro-mechanical mechanism featuring exceptionally compact size with large shutter movement, simple construction, and easy direct drive. The FS-VOA is designed to completely block a collimated light beam over 700 μm in diameter and be operated in air without the need for hermetic seal and is fully compliant with the Telcordia 1209 and 1221 reliability standards. The device is ideally suited to be integrated into laser and receiver systems.

It is available in either normally-open or normally-closed configurations.

Specifications

Parameter	Min	Typical	Max	Unit
Attenuation Resolution		Continuous		
Aperture Diameter		750		μm
Response Time ^[1]		40	75	ms
Optical Power Handling		500		mW
Driving Voltage ^[2]		4	5	V
Device Resistance		100 ^[3]		ohm
Power Consumption			210	mW
Resonant Frequency	250	310		Hz
Operating Temperature	-5		75	°C
Storage Temperature	-40		85	°C
Reliability	Telcordia 1209 and 1221			
Package Dimension	See drawing below			

Note:

[1]. For any desired attenuation. 50ms time constant of control signal is recommended to eliminate the low frequency resonance ≤ 200 Hz. Please refer to Agiltron's design of driving circuit to eliminate the low frequency resonance.

[2]. For full attenuation.

[3]. At voltage 3.6V.

Note: The specifications provided are for general applications with a cost-effective approach. If you need to narrow or expand the tolerance, coverage, limit, or qualifications, please [click this link](#):

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind Agiltron only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with the use of a product or its application.

Rev 08/27/24

0.7 mm Movement Free Space etMEMS™ Attenuator Sub-mount




(Protected by US patent 10752492B2)


DATASHEET

Mechanical Footprint Dimensions (mm)


Device chip



Holder chip



After package



*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

0.7 mm Movement Free Space etMEMS™ Attenuator Sub-mount




(Protected by US patent 10752492B2)

DATASHEET

Mechanical Footprint Dimensions (mm)

Chip on Sub-mount: Normally-open with $\phi 750$ aperture



Flying wires soldering position
Approximate wire diameter: 40 μm


Note: The variety of chips and customization are available, please contact us.

*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

Electronic Driving Instruction

NOTES:

- Resistive without polarity
- Applying $>4.2\text{V}$ will burn the chip
- Two pads are for applying a voltage
- Reference driving circuit on the right




0.7 mm Movement Free Space etMEMS™ Attenuator Sub-mount




(Protected by US patent 10752492B2)

DATASHEET

Shutter Performance (Typical)



Electronic Pin Option for sub-mount (Illustration)



*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

Ordering Information

Prefix	Shutter size	Wavelength	VOA Type	Shutter Surface	Chip Package	Chip Design	Electric connection	Package
FSVOA-	ø700um ^[1] = 70	Broadband = 1	Standard = 1 Special = 0	Gold = 1	Bare = 2 Sub-mount ^[2] = 1 Special = 0	Standard = 1 Special = 0	No PIN = 0 L Pin = 1 Flying Wires = 2 Mounting shorts = 3	Sub-mount = 1

[1]. Different shutter size is available, please check another size FS-VOA chip datasheet.

[2]. Flying wires type; two leads are provided

0.7 mm Movement Free Space etMEMS™ Attenuator Sub-mount



(Protected by US patent 10752492B2)

DATASHEET

VOA Performance

