

# Bi-Substituted Iron Garnet Based Polarization Maintaining 1060nm Optical Isolator

(patents pending)

## Product Description

The OI Series BIG based 1060 nm optical Isolator is a passive device that guides lights at 1060 nm in the normal direction while minimizing back reflection and back scattering in the reverse direction for any state of polarization. With Agiltron's proprietary magnetic-optics technology and proven advanced micro optics design, it features low insertion loss, high isolation, compact structure, high power handling, and high stability. The excellent characteristics of this product make it an ideal choice for application in fiber amplifier systems, pump laser diodes and optical fiber sensors. We currently offer a full range of polarization independent, polarization maintain, and multimode versions. Agiltron also provides customized design to meet special applications.



## Performance Specifications

OI Series BIG based PM Isolator	Min	Typical	Max	Unit
Operation Wavelength	1060	1064	1070	nm
Insertion Loss <sup>1</sup>		1.4	1.8	dB
Wavelength Dependent Loss			0.2	dB
Isolation	23	28		
Extinction Ratio	20	25		dB
Return Loss	50			dB
Optical Power Handling			300	mW
Fiber Type	See order information			
Package Dimension	(Ø)5.5 X (L)34			mm

1. Excluding connectors

## Features

- Low Insertion Loss
- High Isolation
- Low PDL
- High Stability
- High Reliability
- Cost Effective

## Applications

- Optical Fiber Amplifier
- Pump Laser Source
- Fiber Optic Sensor
- Test and Measurement
- Instrumentation

# Bi-Substituted Iron Garnet Based Polarization Maintaining 1060nm Optical Isolator

## Ordering Information

OISB-	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	Type	Wavelength	Grade	Package	Fiber Type	Fiber Length	Connector	
	Polarization Maintaining=1 2 Special=10	1060=1 Special=0	Standard=1 Special=0	Standard=1 Special=0	PM980=E Special=0	Bare fiber=1 900um loose tube=3 Special=0	0.25M=1 0.5M=2 1.0M=3 Special=0	None=1 FC/PC=2 FC/APC=3 SC/PC=4 SC/APC=5 ST/PC=6 LC=7 Special=0