

Single mode, up to 5mW, 2nm, Benchtop or Module



**DATASHEET** 

Return to the Webpage 🤉



emitting spectrum from 370nm to 2000nm and line width from 10kHz to broadband to select. Each benchtop laser source features a pigtailed laser and high-precision, low-noise auto-feedback drive electronics to ensure constant output power or a constant driving current, and an integrated temperature control unit maintains optimal operating conditions. Each unit features a front fiber output connector and a universal power supply compatible with 100 to 240 VAC. We offer two packages: benchtop for ease of use and compact module for system integration. The user interface benchtop includes an intuitive LCD display for independent control of output power and temperature via two front rotating knobs. The module has two front output power and temperature settings. All units have a built-in isolator option to prevent reflection-induced laser emissions instability. We produce fiber-coupled isolators from 370nm to 2000nm. An isolator is essential to obtain stable laser output.

Agiltron provides cost-effective fiber-coupled laser sources with a wide range

#### **Features**

- Turnkey Laser Source
- High Stability
- Advanced Feedback Control

### **Applications**

- Medical Laser Treatment
- Biotechnology
- Others



### **Specifications**

Parameter	Min	Typical	Max	Unit
Threshold Current		35	55	mA
Forward Current		60	80	mA
Forward Voltage		2.4	3.0	V
Optical Output Power		5		mW
Center Wavelength@25°C	650	660	670	nm
Spectral Linewidth (FWHM)			2	nm
Monitor Current		0.2		mA
Reverse Voltage			30	V
Recommend Operating Temperature		25		°C
Operating Case Temperature	-10		50	°C
Storage Temperature	-40		85	°C

**Note:** The specifications provided are for general applications with a cost-effective approach. If you need to narrow or expand the tolerance, coverage, limit, or qualifications, please [click this <a href="link">link</a>]:

Rev 09/20/25





Single mode, up to 5mW, 2nm, Benchtop or Module



**DATASHEET** 

#### **Benchtop Laser Source Operation Manual**



- Plug in power cable
- Turn on Power Switch
- Setting the Output Power by rotating the knob
- Setting the laser diode Temperature by rotating the knob
- Connect a fiber path cable with matching connector (FC/APC is the default)
- Push the Emission switch to turn on the laser
- Measure the output power to verify

#### **Module Laser Source Operation Manual**



- Plug in power cable
- Turn on Power Switch
- Setting the Output Power by rotating the screw
- Setting the laser diode Temperature by rotating the screw
- Connect a fiber path cable with matching connector (FC/APC is the default)
- Push the Emission switch to turn on the laser
- Measure the output power to verify



Single mode, up to 5mW, 2nm, Benchtop or Module




DATASHEET

Module (mm): Plug-Play (Power Supply Included)











### Benchtop (mm): Plug-Play 100-240VAC, USB







\*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

© Photonwares Corporation

P +1 781-935-1200



E sales@photonwares.com






Single mode, up to 5mW, 2nm, Benchtop or Module



#### **Typical Spectrum**



#### **Ordering Information**

Prefix	Wavelength	Power	Linewidth	Package	Isolator	Control Mode	TEC Cooling	Fiber Type	Connector
FCLS-	660nm = 0660	5mW = 5	2nm = 1	Benchtop = 1 Module = 2	None = 1 Yes = 2	Constant Current = 2 Constant Power = 1	No = 1 Yes = 2	SM450 = 3 SM600 = 6 PM460 = B PM630 = C Special = 0	FC/APC = 3 FC/PC = 2 Non = 1 SC/PC = 4 SC/APC = 5 LC/PC = 7 LC/UPC = U Special = 0