

High Power Fiber Inline Polarizer

(up to 300W, all fiber types)



DATASHEET

BUY NOW



The High Power Fiber In-line Polarizer is designed to pass light with one specific polarization while blocking the other polarization. It can be used to convert non-polarized light into polarized light with high extinction ratio. It can also be used to enhance the extinction ratio of signals with its polarization properties. We offer all possible fiber coupling combinations: PM to PM, SM to PM, SM to SM. It has a third port to guide the unwanted light out. Our design minimizes component assembly costs and module footprint while increasing stability over a wide temperature and wavelength ranges.

Features

- Low Cost
- All Wavelength
- All Fiber Type
- Compact Design

Applications

- Laser
- Device
- Instruments

Specifications

Parameter	Min	Typical	Max	Unit
Wavelength	450		2300	nm
Wavelength Bandwidth	-40		+40	nm
Insertion Loss ^[1]		0.5	1	dB
Polarization Extinction	30		33	dB
Optical Power Handling ^[2]			200	W
Return Loss	50			dB
Operating Temperature	-10		75	°C
Storage Temperature	-40		85	°C

Note:

- [1]. Insertion Loss excluding connectors
- [2]. For fiber core size > 7µm

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind Agiltron only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with the use of a product or its application.

Rev 08/27/24

High Power Fiber Inline Polarizer

(up to 300W, all fiber types)



DATASHEET

Dimensions (mm)

*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

Ordering Information

Prefix	Wavelength	Package	Input Fiber	Output Fiber ^[1]	Power	ER	Fiber Cover	Fiber Length	Connector
FILP-	1060 = 1 1310 = 3 1420 = 4 1550 = 5 980 = 9 850 = 8 780 = 7 650 = 6 550 = W Special = 0	Special = 0	SM28 = 1 PM1550 = 2 PM1310 = 3 Hi1060 = 6 Special = 0	PM1550 = 1 PM1310 = 3 PM1060 = 6 Special = 0	5W = A 10W = 1 20W = 2 30W = 3 40W = 4 50W = 5 60W = 6 70W = 7 80W = 8 90W = 9 Special = 0	>30 = 1	900umTube = 3 3mm tube = 4 Special = 0	0.25m = 1 0.5m = 2 1.0 m = 3 1.5 m = 5 Special = 0	None = 1 FC/PC = 2 FC/APC = 3 SC/PC = 4 SC/APC = 5 LC/PC = 7 LC/UPC = U Special = 0

Red is special orders

Notes:

[1]. PM1550 fiber works well for 1310nm and lower cost

High Power Fiber Inline Polarizer

(up to 300W, all fiber types)



DATASHEET

Application Notes

Fiber Core Alignment

Note that the minimum attenuation for these devices depends on excellent core-to-core alignment when the connectors are mated. This is crucial for shorter wavelengths with smaller fiber core diameters that can increase the loss of many decibels above the specification if they are not perfectly aligned. Different vendors' connectors may not mate well with each other, especially for angled APC.

Fiber Cleanliness

Fibers with smaller core diameters ($<5 \mu\text{m}$) must be kept extremely clean, contamination at fiber-fiber interfaces, combined with the high optical power density, can lead to significant optical damage. This type of damage usually requires re-polishing or replacement of the connector.

Maximum Optical Input Power

Due to their small fiber core diameters for short wavelength and high photon energies, the damage thresholds for device is substantially reduced than the common 1550nm fiber. To avoid damage to the exposed fiber end faces and internal components, the optical input power should never exceed 20 mW for wavelengths shorter 650nm. We produce a special version to increase the handling by expanding the core side at the fiber ends.