

In-Line Fixed PM Fiber Attenuator

from 0dB to 20 dB at intervals of 0.5 dB Attenuation Level

DATASHEET

[Return to the Webpage](#)



The ILFA series of In-Line Fixed Attenuators is designed for precise optical power adjustment to a desired level. Featuring a fused passthrough fiber design, it ensures high reliability, making it suitable for airborne and space applications. The attenuator provides fixed attenuation levels ranging from 0 dB to 20 dB, with 0.5 dB increments for fine-tuned power control. We offer custom configurations to meet specific application requirements, including different connector types and end-face configurations. PM Panda fiber (PM780-HP, PM980, PM1550, PM1950)

Features

- Low Insertion Loss
- High PER
- High Return Loss
- High Stability & Reliability

Specifications

Parameter	Min	Typical	Max	Unit
Center Wavelength	780, 830, 980, 1064, 1310~2000			nm
Operating Wavelength	780, 830, 980, 1064 nm	±10		nm
	1310~2000 nm	±20		
Return loss	50			dB
Power Handling			500	mW
Tensile Load			5	N
Operating temperature	-40		80	°C
Operating temperature	-40		85	°C
Dimensions	3.0x54(for bare fiber/0.9mm tube)			mm
	90x20x10(for 2.0mm/3.0mm tube)			

Applications

- Optical Power Control
- Optical Power Equalization
- Telecommunication Systems
- WDM Systems
- Fiber Optic Instruments

Attenuate Value and Its Tolerance & PDL

Attenuate Value (dB)	IL Tolerance (dB)		Min. PER (dB)			
	Premium	A grade	780nm, 830nm, 980nm, 1064nm		1310-2000nm	
			Premium	A grade	Premium	A grade
1	± 0.1	± 0.2	20	18	20	18
2	± 0.2	± 0.3	20	18	20	18
3	± 0.3	± 0.4	20	18	20	18
5	± 0.7	± 0.8	20	18	20	18
10	± 1.0	± 1.2	20	18	20	18
15	± 1.8	± 2.2	20	18	20	18
20	± 2.5	± 3.0	18	15	18	15

Notes:

[1]. Above specifications are for device without connector.

[2]. For devices with connectors, IL will be 0.3dB higher, RL will be 5dB lower. The default connector key is aligned to slow axis. Power transmits through the connector less than 2W.

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind Agiltron only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with the use of a product or its application.

Rev 02/18/25

In-Line Fixed PM Fiber Attenuator

from 0dB to 20 dB at intervals of 0.5 dB Attenuation Level

DATASHEET

Mechanical Dimension (mm)



*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

Ordering Information

Prefix	Wavelength	Attenuation	Optical Power	Fiber Type	Package	Fiber Buffer	Fiber Length	Connector
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
ILFA-	780nm = 7 830nm = 8 980nm = 9 1060nm = 1 1310nm = 3 1410nm = 4 1550nm = 5 1990nm = 9 2000nm = 2 Special = 0	1dB = 1 2dB = 2 3dB = 3 5dB = 5 10dB = 10 15dB = 15 20dB = 20 Special = 0	0.5W = 1 1W = 2 5W = 5 10W = 9	Select below Special = 00	3x54 Tube = 1 Special = 0	0.9mm Tube = 3 Bare Fiber = 1 Special = 0	1.0 m = 1 Special = 0	FC/APC = 3 FC/PC = 2 Special = 0

Fiber Type Selection Table:

01	SMF-28	34	PM1550	71	MM 50/125µm
02	SMF-28e	35	PM1950	72	MM 62.5µm
03	Corning XB	36	PM1310	73	105/125µm
04	SM450	37	PM400	74	FG105LCA
05	SM1950	38	PM480	75	FG50LGA
06	SM600	39	PM630	76	STP 50/125
07	780HP	40	PM850	77	IRZS23
08	SM800	41	PM980	78	IRZS32
09	SM980	42	PM780		
10	Hi1060	43			
11	SM400	44	PM405		
12		45	PM460		
13		46			