

# MEMS Straight Fiber Optical Variable Attenuator



(Protected by US Patent 10752492B2)

DATASHEET

BUY NOW



The MEMS Straight Series Fiber Optical Variable Attenuator uses a patented thermal activated micro-mirror, moving-in and -out optical paths, uniquely featuring large extinction ratio, high stability over wide temperature range, and very long life cycle. The thermal MEMS is insensitive to moisture and ESD without drift issues, providing a high reliability platform for over 25 years continuous operation. The MEMS Straight Series VOAs are configured in single and dual channels (activated at the same time). The VOAs are bidirectional and are Telcordia standards GR1221 qualified.

Agiltron provides customized design and modular assemblies to meet control and integration applications.

This VOA is designed to be used in a feedback configuration

## Features

- High Reliability
- Direct DC drive
- Ultra Small
- ESD Insensitive

## Specifications

Parameter		Min	Typical	Max	Unit
Operation Wavelength	Single Mode	1260 ~ 1610			nm
	Multimode	810-890	1260-1360	1500-1600	
Insertion Loss <sup>[1], [2]</sup>			0.6	1.0 / 1.2 <sup>[3]</sup>	dB
PDL (SM)				0.1	dB
PMD (SM)		0.0001		0.01	dB
Extinction Ratio	PM fiber	18			dB
Return Loss	SM, PM	50			dB
	MM	35			
Attenuation	SM, PM	55 <sup>[4]</sup>			dB
	MM	45			
Response Time			3	7	ms
Repetition Rate				20	Hz
Wavelength Dependence@20dB				0.5	dB/100nm
Durability		10 <sup>12</sup>			Cycle
Power Consumption (at maximum)				170	mW
Operating Temperature <sup>[4]</sup>		-5		+70	°C
Storage Temperature		-40		+85	°C
Optical Power Handling (CW)			300	500	mW
Fiber Type	Single Mode	SMF-28 or equivalent			
	PM	Panda 150 PM or equivalent			
	Multimode	MM 50/125, MM 62.5/125 or equivalent			

### Notes:

- [1]. Excluding connectors.
- [2]. Multimode IL measured @ Light Source CPR < 14dB.
- [3]. Dual band.
- [4]. Lower temperature version is available, please call us

**Note:** The specifications provided are for general applications with a cost-effective approach. If you need to narrow or expand the tolerance, coverage, limit, or qualifications, please [click this link](#):

**Legal notices:** All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind Agiltron only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with the use of a product or its application.

Rev 06/21/24

# MEMS Straight Fiber Optical Variable Attenuator




(Protected by US Patent 10752492B2)


## DATASHEET

### Mechanical Dimension (unit: mm)

#### Package 1: Standard package



#### Package D: Add Adapting PCB version



### Electrical Driving Requirements

1. Resistance load device, insensitive to ESD.
2. Highly recommend to add 70 ohm resistor in series on Pin 3 in driver to smooth the attenuation slope.
3. **Warning: Damaged if applying voltage over the maximum (even for a short time)**
4. Pin 2 = 0V, Pin 3 = 0~4.5V (maximum)

\*Product dimensions may change without notice. This is sometimes required for non-standard specifications.


# MEMS Straight Fiber Optical Variable Attenuator



(Protected by US Patent 10752492B2)


## DATASHEET

### Typical Attenuation vs. Voltage w/ T compensation for Transparent Type



Note: Measured by adding the resistor and temperature compensation on MSOA.

### Typical Attenuation vs. Voltage for Opaque Type




# MEMS Straight Fiber Optical Variable Attenuator



(Protected by US Patent 10752492B2)

## DATASHEET

### Typical Attenuation vs. Wavelength for WDL at 20 dB



### Ordering Information

Prefix	Non-Power State	Wavelength	Temperature Range	Package	Fiber Type	Fiber Cover	Fiber Length	Connector
<b>MSOA-</b>	Single VOA Transparent = 01 Single VOA Opaque <sup>[1]</sup> = 02 Dual VOA Transparent = 21 Dual VOA Opaque = 22	1260~1620 = B 1060 = 1 1310 = 3 1550 = 5 850 = 8 850/1310 = A Special = 0	-5 to 75°C = 1 -40 to 75°C = 2 Special = 0	Package 1 <sup>[2]</sup> = 1 Package D <sup>[3]</sup> = D Special = 0	SMF-28 = 1 PM1550 = B PM1310 = D PM980 = E PM850 = F MM 50/125 = 5 MM 62.5/125 = 6 Special = 0	Bare fiber = 1 900 μm tube = 3 Special = 0	0.25m = 1 0.5m = 2 1.0m = 3 Special = 0	None = 1 FC/PC = 2 FC/APC = 3 SC/PC = 4 SC/APC = 5 LC/PC = 7 Special = 0

[1]. Opaque means the light is blocked when no electrical power is present.

[2]. Package 1 (see Drawing) is Standard package.

[3]. Package D (see Drawing) is add Adapting PCB version.

**Note:**

“transparent” means no attenuation without applying a controlling voltage, the “opaque” means the highest attenuation without applying a controlling voltage.