

NanoSpeed™ SM Variable Photonic Time Delay

0.045 ~ 2.6GHz, SM28 Fiber



DATASHEET

[Return to the Webpage](#)



The NSTD Series Photonic Time Delay generates variable time delay by selectively routing optical signals through N (≤ 8) fiber segments whose lengths increase successively by a power of 2 to form a N bit digital delay line. The NSTD allows customers to splice each fiber loop, creating increments of ΔT , up to the maximum value T . The switching between each loop is achieved using a patented non-mechanical configuration. The solid-state configuration eliminates the need for mechanical movement and organic materials. The device is designed to meet the most demanding switching requirements of ultra-high reliability and fast response time.

Features

- High Resolution
- High Speed
- Non-Mechanical
- High Reliability

Applications

- Phase-Array Antennas
- Instrumentation

Specifications

Parameter	Min	Typical	Max	Unit
Central Wavelength	850		1610	nm
Bit resolution ^[1]		4	8	
Insertion Loss ^[2]		4.0	5.2	dB
Cross Talk	20	25		dB
Switching Time (fall, rise)		300	400	ns
Repetition Rate ^[3]			100	kHz
Delay Time Range	ns		μ s	
PDL ^[4]		0.3	1.0	dB
Return Loss	45			dB
Fiber type	SM fiber or PM fiber			
Operating Temperature	0		60	°C
Optical Power Handling ^[5]		500		mW
Storage Temperature	-5		85	°C
Package Dimension ^[6]	19" mount rack			

Notes:

- [1]. TBD per customer's request.
- [2]. Measured at 4-bit device, excluding the loss of long delay fibers. 1dB additional loss will be added per bit after 4-bit.
- [3]. for each switching core.
- [4]. Defined at 4-bit delay line
- [5]. Measured at 1550nm.
- [6]. Mount rack height will be determined based the final delay.

Rev 02/05/25

© Photonwares Corporation

[P +1 781-935-1200](tel:+17819351200)

[E sales@photonwares.com](mailto:sales@photonwares.com)

[W www.agiltron.com](http://www.agiltron.com)

NanoSpeed™ SM Variable Photonic Time Delay

0.045 ~ 2.6GHz, SM28 Fiber



DATASHEET

Dimensions (mm)

*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

Control Electronics

The standard electrical driver has USB and RS232 interfaces with Windows™ GUI. The power supply is AVC 100 ~ 240V. The driver control interface can be customized to increase the delay repeat rate buy using TTL control through PIN connectors, please contact us.

Ordering Information

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	0	<input type="checkbox"/>
Prefix	Resolution	Wavelength	Configuration	Package	Fiber Type	Fiber Cover	Delay Range	Connector
NSTD-	4 bits = 42 5 bits = 52 8-bits = 82 Special = 00	850nm = 8 1060nm = 1 1310nm = 3 1550nm = 5 Special = 0	Standard = 1	19" rack = 2 Special = 0	SMF-28 = 1 HI1060 = 2 HI780 = 3 PM1550 = 5 PM980 = 9 Special = 0	Bare fiber = 1 900um loose tube = 3	Custom	None = 1 FC/PC = 2 FC/APC = 3 SC/PC = 4 SC/APC = 5 ST/PC = 6 LC/PC = 7 Special = 0